



## Set consisting of 12 x 1007095 UNIVERSAL DOWNLIGHT PHASE IP65 38° and 1007096 UNIVERSAL DOWNLIGHT cover IP65 black R

The UNIVERSAL DOWNLIGHT Multipack contains 12 of the UNIVERSAL DOWNLIGHT PHASE recessed lights with matching covers in black. An all-round carefree package that makes planning even easier with our UNIVERSAL DOWNLIGHT. Due to its narrow beam angle of 38 degrees, the recessed light provides a targeted beam of light. The IP65 protection rating also protects it from water jets. The CCT switch allows the color temperature to be selected before installation (2700/3000/4000/6000K), giving you maximum flexibility on the construction site. The choice of total wattage - 5W or 8W - is just as easy. True-to-life colour reproduction is guaranteed thanks to CRI90. The corresponding Quick Connector Box rounds off the overall picture and makes installation of these recessed lights easier than ever.

### TECHNICAL DATA

Item no.	1007271
IP Code	IP20/IP65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	60/90 mA
Safety class	II
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	60
Number of luminaires at LS C16A	150
Level of inrush current	3 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0
Lumen	560/610/680/640 lm
Colour temperature	2700/3000/4000/6500 Kelvin

## Light Source

1807465



Beam angle	38 °
Color	black
CRI	90
UGR ≤	28
LXXBXX data	L70B50
Service life	35000 h
Risk Group	0
Height	4.85 cm
Diameter	8.8 cm
Net weight	3 kg
Gross weight	3.21 kg
Shape of cut-out	round
Installation depth	5.5 cm
Installation diameter	6.8 cm
BIG WHITE Page	208

