



Set consisting of 12x 1007090 UNIVERSAL DOWNLIGHT MOVE PHASE IP20 38° and 1007091 UNIVERSAL DOWNLIGHT cover IP20 black R

The UNIVERSAL DOWNLIGHT Multipack contains 12 of the UNIVERSAL DOWNLIGHT MOVE PHASE recessed lights with matching covers in black. An all-round carefree package that makes planning even easier with our UNIVERSAL DOWNLIGHT. The light can be swivelled to direct the beam precisely where you want it to go. The CCT switch allows the color temperature to be selected before installation (2700/3000/4000/6000K), giving you maximum flexibility on the construction site. The choice of total wattage - 5W or 8W - is just as easy. True-to-life colour reproduction is guaranteed thanks to CRI90. The corresponding Quick Connector Box rounds off the overall picture and makes installation of these recessed lights easier than ever.

TECHNICAL DATA

Item no.	1007273
Rotating or tilting	tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	60/90 mA
Safety class	II
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	60
Number of luminaires at LS C16A	150
Level of inrush current	3 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0
Lumen	560/610/680/640 lm

Light Source

1807465



Colour temperature	2700/3000/4000/6500 Kelvin
Beam angle	38 °
Color	black
CRI	90
UGR ≤	28
LXXBXX data	L70B50
Service life	35000 h
Risk Group	0
Height	6.1 cm
Diameter	8.8 cm
Net weight	3.2 kg
Gross weight	3.424 kg
Shape of cut-out	round
Installation depth	7.3 cm
Installation diameter	6.8 cm
BIG WHITE Page	209