




NEW TRIA® 68

recessed ceiling light, 1800-3000K, 60°, IP 20, square, white

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are available as a complete set. The integrated LED MODULE, which is available with dim-to-warm technology (1800-3000K) and different beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light, in black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68mm mounting ring supplied, the downlights can also be installed quickly and simply.



TECHNICAL DATA

| | |
|---------------------------------|--|
| Item no. | 1007429 |
| Rotating or tilting | Tilttable |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | Dim-to-Warm, Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 250 mA |
| Safety class | II |
| Wattage | 11 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 85 |
| Number of luminaires at LS C16A | 144 |
| Level of inrush current | 2 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 70-700 lm |
| Colour temperature | 1800-3000 Kelvin |
| Beam angle | 60 ° |
| Color | white |

Light Source

879017



| | |
|-----------------------|----------|
| CRI | 90 |
| LXXBXX data | L80B10 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 8.2 cm |
| Width | 8.2 cm |
| Height | 4 cm |
| Net weight | 0.21 kg |
| Gross weight | 0.225 kg |
| Shape of cut-out | round |
| Installation depth | 4.5 cm |
| Installation diameter | 6.8 cm |
| BIG WHITE Page | 135 |

