




WORKLIGHT PRO

free-standing lamp, 150W, 4000K, Touch, black

The new WORKLIGHT PRO stands for high performance in the workplace: the free-standing lamp is optimally designed in line with the latest DIN EN 12464:2021 standard. Its glare-free ($UGR < 14$) luminous efficiency of 130 lm/W, a colour temperature of 4000K and improved, indirect light output offers everything you need for an ergonomic working environment. Dimmability, daylight control, a motion sensor and long lifespan (L80/B10 50,000h) also help to make the free-standing office lamp what it is: a true SLV colleague that assists with productivity.





TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1007465 |
| Number of different light outlets | 2 |
| IP Code | IP 20 |
| Impact resistance class | IK 03 |
| Impact resistance | 0.35 Joule |
| Assembly | Mobile |
| Dimmable | Yes |
| Dimming technology | Touch |
| Primary nominal voltage | 200-240V ~50/60Hz |
| Secondary power / voltage | 48 V |
| Safety class | I |
| Wattage | 150 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 3 |
| Number of luminaires at LS C16A | 5 |
| Level of inrush current | 72 A |
| Duration of inrush current | 410 μ s |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 20000 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 75 ° |



Light Source

| | |
|---------|---|
| 1807475 |  |
| 1807479 |  |

| | |
|----------------|-----------|
| Color | black |
| CRI | 80 |
| UGR \leq | 16 |
| LXXBXX data | L80B10 |
| Service life | 50000 h |
| Risk Group | 0 |
| Length | 163.4 cm |
| Width | 24 cm |
| Height | 200 cm |
| Net weight | 20.7 kg |
| Gross weight | 22.149 kg |
| BIG WHITE Page | 444 |

