




## WORKLIGHT PRO 120

pendant light, 120cm, 4000K, DALI, Touch, grey



The new WORKLIGHT PRO stands for high performance in the workplace: the DALI-controllable pendant light is optimally designed in line with the latest DIN EN 12464:2021 standard. Its glare-free (UGR<19) luminous efficiency of 127 lm/W, a colour temperature of 4000K and improved, indirect light output offers everything you need for an ergonomic working environment. Dimmability and a long life-span of 50,000 hours also help to make the office pendant light what it is: a true SLV colleague that assists with productivity.



## TECHNICAL DATA

Item no.	1007470
Number of different light outlets	2
IP Code	IP 20
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI, Touch
Primary nominal voltage	200-240V ~50/60Hz
Secondary power / voltage	1200 mA
Safety class	I
Wattage	50 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	45
Number of luminaires at LS C16A	45
Level of inrush current	4.75 A
Duration of inrush current	162 µs
Stroboscopic effect (SVM)	0.4
Lumen	6100 lm
Colour temperature	4000 Kelvin

## Light Source

1807476	
1807474	

Beam angle	80 °
Color	grey
CRI	80
UGR ≤	19
LXXBXX data	L80B10
Service life	50000 h
Risk Group	0
Length	120 cm
Height	24 cm
Depth	3.28 cm
Pendant length	250 cm
Net weight	5.1 kg
Gross weight	5.457 kg
BIG WHITE Page	287