




## **WATERPROOF V DALI** 1500

## 50W 840 IP66

Discover our new technical product range: SLVtec.With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights - our high-quality products impress with functionality and a fair price-performance ratio. These include the WATERPROOF  $\ensuremath{\mathsf{V}}$ light, which is protected against strong jets of water thanks to protection code IP66 and is also available as a DALI version. The light colour (3000K/4000K) and light intensity can be easily changed via dip switches. The pre-installed through-wiring kit allows two lights to be connected quickly and easily. Installation is also extremely easy thanks to the removable equipment rack. Decide in favour of SLVtec today.



## **TECHNICAL DATA**

Item no.	1007495
IP Code	IP 66
Impact resistance class	IK 08
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	DALI,Touch
Number of through-wires	15
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	50 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	40 °C
Network rated standby power	0.4 W
Number of luminaires at LS B16A	17
Number of luminaires at LS C16A	28
Level of inrush current	31 A
Duration of inrush current	262 µs
Stroboscopic effect (SVM)	0.02
Lumen	6640 lm
Colour temperature	4000 Kelvin
	-





## **Light Source**

A D 1807483

Color	grey
CRI	80
LXXBXX data	L80B10
Service life	50000 h
Risk Group	0
Length	153.6 cm
Width	8 cm
Height	7.6 cm
Net weight	1.95 kg
Gross weight	2.087 kg