




## SURFACE V 390

10/15/20W 830/840 IP44

Discover our new technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the high-quality designed SURFACE V wall-mounted light, which is optionally available with a motion sensor. The light colour (3000-K/4000K) and light intensity (1850lm/2000lm) can be easily adjusted via dip switches. With a large beam angle of 120°, it homogeneously illuminates any environment, and its service life of 50,000 hours makes it ideal for long-term use. And the removable cover also makes installation easy. Decide in favour of SLVtec today.



## TECHNICAL DATA

|                                 |                   |
|---------------------------------|-------------------|
| Item no.                        | 1007516           |
| IP Code                         | IP 44             |
| Assembly                        | Surface           |
| Assembly details                | Ceiling, Wall     |
| Number of through-wires         | 10                |
| Primary nominal voltage         | 220-240V ~50/60Hz |
| Secondary power / voltage       | 165/120/84 mA     |
| Safety class                    | I                 |
| Wattage                         | 20 W              |
| Minimum ambient temperature     | -20 °C            |
| Maximum ambient temperature     | 40 °C             |
| Number of luminaires at LS B16A | 13                |
| Number of luminaires at LS C16A | 22                |
| Level of inrush current         | 25.4 A            |
| Duration of inrush current      | 200 µs            |
| Stroboscopic effect (SVM)       | 0.4               |
| Lumen                           | 1850/2000 lm      |
| Colour temperature              | 3000/4000 Kelvin  |
| Beam angle                      | 120 °             |
| Color                           | white             |
| CRI                             | 80                |
| LXXBXX data                     | L80B10            |



## Light Source

|        |   |
|--------|---|
| 771797 |  |
|--------|---|

|              |         |
|--------------|---------|
| Service life | 50000 h |
| Height       | 11.5 cm |
| Diameter     | 39 cm   |
| Net weight   | 0.74 kg |
| Gross weight | 1.34 kg |

