




## KADUX

recessed ceiling light, single, 3000K, 38°, IP 20, square, black

The new generation of the KADUX family features a robust light housing with a square design. The single-lamp recessed ceiling light emits an even more efficient, warm-white light (3,000K) with a light output of 103 lm/W and extremely neutral, dimmable colour with a CRI of over 90. Ideal for use in shops, hotels and catering facilities. It is also quick and easy to install thanks to its direct connection to a 230V mains voltage.



## TECHNICAL DATA

Item no.	1007551
Rotating or tilting	tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	7.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	149
Level of inrush current	3 A
Duration of inrush current	33 µs
Stroboscopic effect (SVM)	0.4
Lumen	770 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black



## Light Source

1168456	
---------	---

CRI	90
LXXBXX data	L80B10
Service life	50000 h
Risk Group	1
Length	9 cm
Width	9 cm
Height	8.3 cm
Net weight	0.35 kg
Gross weight	0.374 kg
Shape of cut-out	square
Installation length	8 cm
Installation width	8 cm
Installation depth	8 cm
BIG WHITE Page	213

