




CYFT

wall- and ceiling-mounted light, 2700/3000/4000K, 6.5-W, PHASE, black

The CYFT wall-mounted light brings modern, elegant and exclusive SLV design to every bathroom. Not only is the high-quality light available in four trendsetting colours but the optional decorative ring is also available in three different colours. The colour temperature of the integrated LED can be adjusted (2700/3000/4000K) via CCT switch and is extremely neutral (CRI >90). Thanks to its IP44 protection class, the CYFT is naturally also protected against water spray.



TECHNICAL DATA

Item no.	1007608
IP Code	IP 44
Impact resistance class	IK 05
Impact resistance	0.7 Joule
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	200
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	6.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	224
Number of luminaires at LS C16A	266
Level of inrush current	5 A
Duration of inrush current	100 µs
Lumen	330/350/380 lm
Colour temperature	2700/3000/4000 Kelvin
Color	black



Light Source

1807506 

CRI	90
UGR \leq	22
LXXBXX data	L70B50
Service life	50000 h
Risk Group	0
Height	7.9 cm
Diameter	13.2 cm
Net weight	0.946 kg
Gross weight	1.012 kg
BIG WHITE Page	395

