




## NOBLO® SPOT

1~ spot, round, 3000K, 6W, trailing-edge phase, 32°, grey

The rotating and pivoting NOBLO® SPOT shines across the board: quickly and easily mounted on the single-phase high-voltage track system, the new generation impresses with an improved colour reproduction index CRI>90, a lumen output of up to 126 lm/W and an increased service life of up to 50,000 hours. Added to this is the high-quality light that creates a particularly cosy atmosphere in living areas, hotels and restaurants. Ideal for modern lighting concepts, made of high-quality aluminium, quickly installed and available in colour temperatures of 2700K and 3000K. It's clear: with the new NOBLO® SPOTS, you are opting for a unique lighting experience.




## TECHNICAL DATA

|                                 |                                  |
|---------------------------------|----------------------------------|
| Item no.                        | 1007643                          |
| Rotating or tilting             | Rotary bar and tiltable          |
| IP Code                         | IP 20                            |
| Assembly                        | Surface                          |
| Assembly details                | Ceiling,Track Ceiling,Track Wall |
| Dimmable                        | Yes                              |
| Dimming technology              | trailing edge                    |
| Primary nominal voltage         | 220-240V ~50/60Hz                |
| Secondary power / voltage       | 150 mA                           |
| Safety class                    | I                                |
| Wattage                         | 6 W                              |
| Minimum ambient temperature     | -20 °C                           |
| Maximum ambient temperature     | 40 °C                            |
| Number of luminaires at LS B16A | 128                              |
| Number of luminaires at LS C16A | 160                              |
| Level of inrush current         | 3.5 A                            |
| Duration of inrush current      | 120 µs                           |
| Stroboscopic effect (SVM)       | 0.4                              |
| Lumen                           | 750 lm                           |
| Colour temperature              | 3000 Kelvin                      |
| Beam angle                      | 32 °                             |
| Color                           | grey                             |



## Light Source

1425086 

|                |          |
|----------------|----------|
| CRI            | 90       |
| LXXBXX data    | L80B10   |
| Service life   | 50000 h  |
| Risk Group     | 1        |
| Length         | 10.5 cm  |
| Height         | 10.7 cm  |
| Diameter       | 5 cm     |
| Net weight     | 0.24 kg  |
| Gross weight   | 0.257 kg |
| BIG WHITE Page | 503      |

