




## LID I

wall-mounted light, 2700/3000K, 29W, PHASE, 100°, anthracite

Adjustable light colour via CCT switch (2700K/3000K), a colour rendering index of over 80 and a long LED lifespan of 50,000 hours: the new, twin-lamp LID I wall light emits a powerful, high-quality light with its pivoting lamp head which can be adjusted as needed. Simply perfect for atmospheric lighting of pathways, terraces or walls of homes and office buildings.



## TECHNICAL DATA

Item no.	1007668
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 07
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	30
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	29 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	30
Number of luminaires at LS C16A	30
Level of inrush current	12 A
Duration of inrush current	40 µs
Temperature at glass (light emission)	73 °C
Stroboscopic effect (SVM)	0.09

## Light Source

1807471



Lumen	1700/2000 lm
Colour temperature	2700/3000 Kelvin
Beam angle	100 °
Color	anthracite
CRI	80
LXXBXX data	L70B20
Service life	50000 h
Risk Group	0
Width	25.5 cm
Height	13 cm
Depth	9 cm
Net weight	1.92 kg
Gross weight	2.054 kg
BIG WHITE Page	713