


LID I 45 free-standing lamp

15W, 2700/3000K, PHASE, anthracite

Adjustable light colour via CCT switch (2700K/3000K), a high colour rendering index of over 80 and a long lifespan of 50,000 hours: the new LID I free-standing lamp emits a powerful light with its pivoting lamp head which can be adjusted as needed. Simply perfect for atmospheric lighting of pathways, terraces or walls of homes and office buildings.



TECHNICAL DATA

Item no.	1007670
IP Code	IP65
Impact resistance class	IK 07
Impact resistance	0.2 Joule
Assembly details	Ground
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	61
Number of luminaires at LS C16A	61
Level of inrush current	6.5 A
Duration of inrush current	40 µs
Temperature at glass (light emission)	62 °C
Stroboscopic effect (SVM)	0.05
Lumen	900/1050 lm
Colour temperature	2700/3000 Kelvin
Beam angle	100 °



Light Source

1807471	
---------	---

Accessories

228730	CONNECTION BOX , 3-pin, IP68
--------	---------------------------------

Color	anthracite
CRI	80
LXXBXX data	L70B20
Service life	50000 h
Risk Group	0
Length	17 cm
Width	9.5 cm
Height	45 cm
Net weight	1.78 kg
Gross weight	1.905 kg
BIG WHITE Page	611