



NOBLO® SPOT

track system set, round, 2700K, 19W, trailing-edge phase, 32°, black

With the NOBLO® SPOT track system set you get everything you need for the perfect start. The set, available in several colour versions, includes two track sections, a central connector, two end caps and three NOBLO® SPOTS of the latest generation: high-quality spotlights made of aluminium with an improved CRI value (CRI>90), a lumen output of up to 126 lm/W and an increased service life of up to 50,000 hours. It's clear: with the new NOBLO® SPOTS, you are opting for a unique lighting experience.

TECHNICAL DATA

| | |
|-----------------------------------|---------------------------|
| Item no. | 1007673 |
| Number of different light outlets | 3 |
| Rotating or tilting | Rotary bar and tiltable |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Track Ceiling, Track Wall |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 150 mA |
| Safety class | I |
| Wattage | 19 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Number of luminaires at LS B16A | 128 |
| Number of luminaires at LS C16A | 160 |
| Level of inrush current | 3.5 A |
| Duration of inrush current | 120 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 2250 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 32 ° |



Light Source

1425086 

| | |
|----------------|----------|
| Color | black |
| CRI | 90 |
| LXXBXX data | L80B10 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 200 cm |
| Width | 5 cm |
| Height | 12.5 cm |
| Net weight | 1.8 kg |
| Gross weight | 1.926 kg |
| BIG WHITE Page | 501 |

