




HIGHBAY V 330

100/120/170/200W 840 90°

Discover our new technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights - our high-quality products impress with functionality and a fair price-performance ratio. This includes the HIGHBAY V pendant light, whose light intensity can be adjusted up to 32000lm via dip switches. With its protection code IP65, it is optimally protected against dirt and moisture. At the same time, it impresses with its modern design and a service life of L70/B50@50,000h. Decide in favour of SLVtec today.



TECHNICAL DATA

Item no.	1007679
IP Code	IP65
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	830 mA
Safety class	I
Wattage	200 W
Minimum ambient temperature	-40 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	14
Number of luminaires at LS C16A	24
Lumen	32000 lm
Colour temperature	4000 Kelvin
Beam angle	90 °
Color	black
CRI	80
LXXBXX data	L80B50
Service life	50000 h
Risk Group	0





Height	11.9 cm
Diameter	33 cm
Net weight	3.25 kg
Gross weight	3.478 kg

Accessories

228730	CONNECTION BOX , 3-pin, IP68
1007677	HIGHBAY V 330 , reflector 100°
1007678	HIGHBAY V , connection element 60° adjustable black
1007676	HIGHBAY V , suspension set 1500mm