




DASAR® S

recessed floor light, round, 4W, 3000K, 24°, IP67, cylindrical, anthracite

The DASAR® recessed floor lights are characterised by their high quality. The colour temperature of the symmetrical light diffusion can be adjusted via the CCT switch (2700K/3000K). While the mechanical load of the stainless steel-covered light is 2,000 kg, it is protected from all weather conditions thanks to its IP67 rating. The beam angle can be customised with three separately available and interchangeable reflectors (15°, 36°, 60°). The mounting housing, which is available separately, makes installation both quick and easy.



TECHNICAL DATA

Item no.	1007680
IP Code	IP67
Impact resistance class	IK 10
Assembly	Recessed
Assembly details	Ground with Acc.
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	200 mA
Safety class	I
Wattage	4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	112
Number of luminaires at LS C16A	224
Level of inrush current	10 A
Duration of inrush current	100 µs
Temperature at glass (light emission)	60 °C
Stroboscopic effect (SVM)	0.01
Lumen	350 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	stainless steel

Light Source

1642674	
---------	---

Accessories

1007682	Mounting housing for DASAR® S
1007684	Reflector for DASAR® S/M , 36°
1007683	Reflector for DASAR® S/M , 15°
1007685	Reflector for DASAR® S/M , 50°

CRI	80
LXXBXX data	L80B50
Service life	50000 h
Depth	11.5 cm
Diameter	10.5 cm
Net weight	0.6 kg
Gross weight	0.642 kg
Shape of cut-out	round
Installation depth	15 cm
Installation diameter	18 cm
BIG WHITE Page	833