


## ONE FLAT

pendant light, triple, 300cm, 2700/3000K, DALI 2, Touch, black

Clear the ring thrice over for a new, round design: the ONE FLAT pendant light adds another new member to the popular SLV light family with three flat light rings that guarantee outstanding performance. The premium LEDs emit a DALI-dimmable, adjustable colour temperature (2700/3000K) and colour-neutral (CRI>90) light that is especially long-lasting at 50,000 hours. Perfect for upmarket living rooms or commercial areas. A well-rounded lighting experience.




## TECHNICAL DATA

|                                 |                   |
|---------------------------------|-------------------|
| Item no.                        | 1007701           |
| IP Code                         | IP20              |
| Assembly                        | Surface           |
| Assembly details                | Ceiling           |
| Dimmable                        | Yes               |
| Dimming technology              | DALI 2,Touch      |
| Primary nominal voltage         | 220-240V ~50/60Hz |
| Secondary power / voltage       | 1700 mA           |
| Safety class                    | I                 |
| Wattage                         | 58 W              |
| Minimum ambient temperature     | -25 °C            |
| Maximum ambient temperature     | 45 °C             |
| Network rated standby power     | 0.5 W             |
| Number of luminaires at LS B16A | 10                |
| Number of luminaires at LS C16A | 16                |
| Level of inrush current         | 50 A              |
| Duration of inrush current      | 209 µs            |
| Stroboscopic effect (SVM)       | 0.4               |
| Lumen                           | 3500/3700 lm      |
| Colour temperature              | 2700/3000 Kelvin  |
| Color                           | black             |
| CRI                             | 90                |



## Light Source

1908942 

|                |          |
|----------------|----------|
| LXXBXX data    | L80B10   |
| Service life   | 50000 h  |
| Risk Group     | 1        |
| Height         | 2 cm     |
| Diameter       | 80 cm    |
| Pendant length | 300 cm   |
| Net weight     | 8.4 kg   |
| Gross weight   | 8.988 kg |

