




DASAR® M

recessed floor light, round cover, 24°, 3000K, incl. DALI driver, stainless steel

Experience the highest quality of light with unique ease of installation. In addition, the DALI-controllable DASAR® recessed floor lights with a lifespan of 50,000 hours (L80-B50) set standards in terms of efficiency. The interchangeable reflectors with different beam angles of 15°, 30° and 50° offer a great deal of design freedom to effectively set the scene for facades. The reflectors can also be pivoted by 30°. And thanks to the separately available recessed fixing kit, the installation can be optimally adapted to your project planning.



TECHNICAL DATA

Item no.	1007810
IP Code	IP67
Impact resistance class	IK 10
Assembly	Recessed
Assembly details	Ground with Acc.
Dimmable	Yes
Dimming technology	DALI, Touch
Number of through-wires	20
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	6.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	63
Number of luminaires at LS C16A	100
Level of inrush current	8 A
Duration of inrush current	5.6 µs
Temperature at glass (light emission)	60 °C
Stroboscopic effect (SVM)	0
Lumen	450 lm

Light Source

1642674	
---------	---

Accessories

1007684	Reflector for DASAR® S/M , 36°
1007683	Reflector for DASAR® S/M , 15°
1007685	Reflector for DASAR® S/M , 50°
1007822	Mounting housing , for DASAR® M

Colour temperature	3000 Kelvin
Beam angle	24 °
Color	stainless steel
CRI	80
LXXBXX data	L80B50
Service life	50000 h
Depth	14 cm
Diameter	13 cm
Net weight	1.1 kg
Gross weight	1.177 kg
Shape of cut-out	round
Installation depth	18 cm
Installation diameter	31 cm