




D-RING S

wall light, PHASE, 2700/3000K, PHASE, IP65, white

The new D-RING family elegantly picks up on the trend towards organic shapes. The dimmable indirect warm white light (2700K / 3000K), which can be adjusted via a CCT switch, discreetly and glare-free sets the scene for the facades. The two different diameters offer plenty of creative scope. Thanks to the special surface treatment, it can also be used near the coast.



TECHNICAL DATA

Item no.	1007912
IP Code	IP65
Impact resistance class	IK 06
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Number of through-wires	160
Primary nominal voltage	220-240V ~50Hz
Secondary power / voltage	95 mA
Safety class	I
Wattage	7.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	213
Number of luminaires at LS C16A	213
Level of inrush current	3.44 A
Duration of inrush current	48.4 µs
Stroboscopic effect (SVM)	0.01
Lumen	790/820 lm
Colour temperature	2700/3000 Kelvin
Color	white



Light Source

1907086 

CRI	80
LXXBXX data	L80B20
Service life	50000 h
Risk Group	1
Depth	5 cm
Diameter	16 cm
Net weight	0.5 kg
Gross weight	0.535 kg

