




## D-RING M

wall light, PHASE, 2700/3000K, PHASE, IP65, black

The new D-RING family elegantly picks up on the trend towards organic shapes. The dimmable indirect warm white light (2700K / 3000K), which can be adjusted via a CCT switch, discreetly and glare-free sets the scene for the facades. The two different diameters offer plenty of creative scope. Thanks to the special surface treatment, it can also be used near the coast.



## TECHNICAL DATA

Item no.	1007913
IP Code	IP65
Impact resistance class	IK 06
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Number of through-wires	80
Primary nominal voltage	220-240V ~50Hz
Secondary power / voltage	190 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	119
Number of luminaires at LS C16A	119
Level of inrush current	2.32 A
Duration of inrush current	67.4 µs
Stroboscopic effect (SVM)	0.01
Lumen	1260/1360 lm
Colour temperature	2700/3000 Kelvin
Color	black



## Light Source

1907087	
---------	---

CRI	80
LXXBXX data	L80B20
Service life	50000 h
Risk Group	1
Depth	5 cm
Diameter	25 cm
Net weight	1 kg
Gross weight	1.07 kg