




D-RING M

wall light, PHASE, 2700/3000K, PHASE, IP65, white

The new D-RING family elegantly picks up on the trend towards organic shapes. The dimmable indirect warm white light (2700K / 3000K), which can be adjusted via a CCT switch, discreetly and glare-free sets the scene for the facades. The two different diameters offer plenty of creative scope. Thanks to the special surface treatment, it can also be used near the coast.



TECHNICAL DATA

Item no.	1007914
IP Code	IP65
Impact resistance class	IK 06
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Number of through-wires	80
Primary nominal voltage	220-240V ~50Hz
Secondary power / voltage	190 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	119
Number of luminaires at LS C16A	119
Level of inrush current	2.32 A
Duration of inrush current	67.4 µs
Stroboscopic effect (SVM)	0.01
Lumen	1540/1590 lm
Colour temperature	2700/3000 Kelvin
Color	white



Light Source

1907087	
---------	---

CRI	80
LXXBXX data	L80B20
Service life	50000 h
Risk Group	1
Depth	5 cm
Diameter	25 cm
Net weight	1 kg
Gross weight	1.07 kg

