




Q-RING

wall light, sensor, 3000K, IP54, black

The new Q-RING family elegantly picks up on the trend towards organic shapes. The indirect and warm white light (3000 K) illuminates façades discreetly and glare-free. Thanks to the special surface treatment, it can also be used in coastal areas. The integrated sensor system ensures optimum lighting and safety around the clock.



TECHNICAL DATA

Item no.	1007916
IP Code	IP54
Impact resistance class	IK 06
Impact resistance	2 Joule
Assembly	Surface
Assembly details	Wall
Number of through-wires	20
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	240 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Operating efficiency (LOR)	0,53
Number of luminaires at LS B16A	96
Number of luminaires at LS C16A	96
Level of inrush current	2.4 A
Duration of inrush current	81 µs
Temperature at glass (light emission)	50 °C
Stroboscopic effect (SVM)	0.03
Lumen	950 lm
Colour temperature	3000 Kelvin



Light Source

--

Color	black
CRI	80
LXXBXX data	L80B50
Service life	30000 h
Depth	11 cm
Diameter	27 cm
Net weight	1.04 kg
Gross weight	1.113 kg

