




Q-RING

wall light, 3000K, PHASE, IP65, black

The new Q-RING family elegantly picks up on the trend towards organic shapes. The indirect and warm white light (3000 K) illuminates façades discreetly and glare-free. Thanks to the special surface treatment, it can also be used in coastal areas.



TECHNICAL DATA

Item no.	1007918
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	20
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	240 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Operating efficiency (LOR)	0,53
Number of luminaires at LS B16A	96
Number of luminaires at LS C16A	96
Level of inrush current	4.1 A
Duration of inrush current	104 µs
Temperature at glass (light emission)	50 °C
Stroboscopic effect (SVM)	0.03

Light Source



Lumen	950 lm
Colour temperature	3000 Kelvin
Color	black
CRI	80
LXXBXX data	L80B50
Service life	30000 h
Depth	11 cm
Diameter	27 cm
Net weight	1.04 kg
Gross weight	1.113 kg