




## CYFT WAVE

wall- and ceiling-mounted light, 2700/3000/4000K, 6.5-W, PHASE, black

Illuminate rooms with the CYFT WAVE. The LED wall and ceiling light with transparent glass shade and wave cut creates aesthetic accents, while at the same time providing optimum protection against moisture with IP65. This makes it ideal for bathrooms or indoor and outdoor corridors. With a high CRI>90 and the CCT switch, you can switch between warm 2700K, natural 3000K or the cooler 4000K to achieve the perfect mood. Complete the look with optional decorative rings in six colours. Discover CYFT WAVE: stylish lighting that adapts to your wishes.



## TECHNICAL DATA

|                                 |                       |
|---------------------------------|-----------------------|
| Item no.                        | 1008024               |
| IP Code                         | IP65                  |
| Impact resistance class         | IK 05                 |
| Impact resistance               | 0.7 Joule             |
| Assembly                        | Surface               |
| Assembly details                | Ceiling,Wall          |
| Dimmable                        | Yes                   |
| Dimming technology              | trailing edge         |
| Number of through-wires         | 200                   |
| Primary nominal voltage         | 220-240V ~50/60Hz     |
| Secondary power / voltage       | 500 mA                |
| Safety class                    | I                     |
| Wattage                         | 6.5 W                 |
| Minimum ambient temperature     | -20 °C                |
| Maximum ambient temperature     | 40 °C                 |
| Number of luminaires at LS B16A | 224                   |
| Number of luminaires at LS C16A | 266                   |
| Level of inrush current         | 5 A                   |
| Duration of inrush current      | 100 µs                |
| Lumen                           | 240/260/280 lm        |
| Colour temperature              | 2700/3000/4000 Kelvin |
| Color                           | black                 |



## Light Source

1807506 

|              |         |
|--------------|---------|
| CRI          | 90      |
| UGR $\leq$   | 22      |
| LXXBXX data  | L70B50  |
| Service life | 50000 h |
| Risk Group   | 0       |
| Height       | 7.9 cm  |
| Diameter     | 13.2 cm |
| Net weight   | 1.72 kg |
| Gross weight | 1.84 kg |

