


MOTUNA | CW, PHASE

MOTUNA, CW, PHASE, wall and ceiling surface-mounted luminaire, round, 2700 K, 10 W, 130°, white / gold-colored

The MOTUNA wall and ceiling surface-mounted luminaire is a round fixture with a diameter of 38 cm and a height of 4.97 cm. It is designed for mounting on walls or ceilings indoors. The luminaire features a colour temperature of 2700 K and produces a luminous flux of 1000 lumens with a power consumption of 10 watts. The beam angle is 130°, ensuring wide and even illumination. The housing is made of aluminium and is available in white and gold. Dimming is carried out via trailing edge phase control. The protection rating is IP20, providing protection against contact and solid foreign objects larger than 12.5 mm. The declared service life is 50,000 hours.



Item no.	1010365
Lamps included	No
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250 mA
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	35°C
Number of luminaires at LS B16A	113.0
Number of luminaires at LS C16A	181.0
Level of inrush current	8.5 A
Duration of inrush current	40 µs
Beam angle	130°
Color	white/gold
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	1
Height	5 cm
Diameter	38 cm
Net weight	1.27 kg
Gross weight	2.8 kg
BIG WHITE Page	163