
OVANA 30 | CL, LED, PHASE, CCT

OVANA 30, CL, LED, PHASE, CCT, surface-mounted ceiling luminaire, 2700/3000/4000 K, 11 W, 105°, white

The OVANA 30 is a surface-mounted ceiling luminaire designed for indoor use. It features an LED light source with a variable colour temperature of 2700, 3000, or 4000 Kelvin and a beam angle of 105 degrees. The luminaire has a power consumption of 11 watts and produces a luminous flux between 1200 and 1330 lumens. The housing is made of steel and polycarbonate, ensuring a robust construction. With a diameter of 30 centimetres and a height of 12 centimetres, it is compactly sized. Dimming is possible via PHASE cut-on and cut-off technology. The IP20 protection rating makes it suitable for applications without direct exposure to moisture. The luminaire is designed for a service life of 50,000 hours.



Item no.	1011994
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	Leading edgetrailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250
Safety class	I
Wattage	11 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	56.0
Number of luminaires at LS C16A	118.0
Level of inrush current	5 A
Duration of inrush current	300 µs
Beam angle	105°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	12 cm
Diameter	30 cm
Net weight	1.7 kg