


OVANA 44 | CL, LED, PHASE, CCT

OVANA 44, CL, LED, PHASE, CCT, surface-mounted ceiling luminaire, 2700/3000/4000 K, 14 W, 115°, white

The OVANA 44 is a surface-mounted ceiling luminaire suitable for indoor use. It features an LED light source with a power consumption of 14 watts and offers a selectable colour temperature of 2700, 3000, or 4000 Kelvin. The beam angle is 115 degrees, ensuring even light distribution. The housing is made of steel and polycarbonate, making the luminaire robust and durable. Installation is surface-mounted on the ceiling. The luminaire is equipped with PHASE cut-on and cut-off dimming, allowing flexible light control. The IP20 protection rating indicates that the luminaire is suitable for dry indoor environments. The product dimensions are 44 centimetres in diameter and 12 centimetres in height.



Item no.	1011996
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	Leading edgetrailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350
Safety class	I
Wattage	14 W
Ambient temperature	85
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	160.0
Number of luminaires at LS C16A	160.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	115°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	12 cm
Diameter	44 cm
Net weight	3.71 kg