


OVANA 30 | CL, LED, ZIGBEE, TW

OVANA 30, CL, LED, ZIGBEE, TW, surface-mounted ceiling luminaire, 2200-6500 K, 10 W, 105°, black

The OVANA 30 is a surface-mounted ceiling luminaire suitable for indoor use. It features an LED light source with a variable colour temperature ranging from 2200 to 6500 Kelvin and a power consumption of 10 watts. The luminaire offers a beam angle of 105 degrees and a luminous flux between 920 and 1030 lumens. The housing is made of steel and polycarbonate, ensuring a robust construction. With a height of 12 cm and a diameter of 30 cm, it is designed to be compact. The luminaire is equipped with a dim-to-warm function as well as Zigbee compatibility for wireless control. The protection rating is IP20, making it suitable for dust-protected indoor areas.



Item no.	1011999
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling,
Dimmable	true
Dimming technology	Dim-to-WarmZigbee
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250
Safety class	I
Wattage	10 W
Ambient temperature	85
Minimum ambient temperature	-25°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	55.0
Number of luminaires at LS C16A	92.0
Level of inrush current	4.32 A
Duration of inrush current	80 µs
Beam angle	105°
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	12 cm
Diameter	30 cm
Net weight	1.75 kg