
# SENSER 2.0 30 | CW, SQUARE, DALI

**SENSER 2.0 30, CW, square, DALI, surface-mounted wall and ceiling luminaire, 3000 K / 4000 K, 27 W, 90°, white**

The SENSER 2.0 30 is a square wall and ceiling surface-mounted luminaire suitable for indoor use. It features a light colour of 3000 K or 4000 K and a power output of 27 watts with a beam angle of 90°. The housing is made of aluminium combined with a polycarbonate diffuser. The luminaire measures 30 cm in width and length, and 4 cm in height. It is equipped with DALI-2 dimming, allowing flexible light control. The IP20 protection rating and IK02 impact resistance provide basic protection against foreign objects and mechanical impacts. This makes the luminaire suitable for a wide range of applications in residential and commercial spaces.




| | |
|---|---|
| Item no. | 1012228 |
| Lamps included | No |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Impact resistance | 0.2 Joule |
| Assembly | Surface |
| Assembly details | Ceiling, |
| Dimmable | true |
| Dimming technology | DALI 2 |
| Number of through-wires | 40 |
| Primary nominal voltage | 220-240V ~ 50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 27 W |
| Minimum ambient temperature | -20°C |
| Maximum ambient temperature | 40°C |
| Number of luminaires at LS B16A | 37.0 |
| Number of luminaires at LS C16A | 61.0 |
| Level of inrush current | 15.94 A |
| Duration of inrush current | 220 µs |
| Beam angle | 90° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B10 |
| Service life | 50 000 h |
| Risk Group | 1 |
| Length | 30 cm |
| Width | 30 cm |