



FRAME BASIC

recessed fitting, LED, 3000K, matt white, SET, 9.4W, incl. driver

With our FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED set is equipped with warm white Premium LED light diodes. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Item no.	112721
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	8.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	11 A
Duration of inrush current	20 µs
Stroboscopic effect (SVM)	0.02
Lumen	600 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	50000 h
Length	9 cm
Width	9 cm



Light Source

916629	
--------	---

Height	4 cm
Net weight	0.169 kg
Gross weight	0.211 kg
Shape of cut-out	square
Installation length	7.5 cm
Installation width	7.5 cm
Installation depth	5 cm
BIG WHITE Page	238

