


## NEW TRIA MINI SET

recessed fitting, LED, 3000K, round, brushed aluminium, 30°, incl. driver, clip springs

The simplicity and effectiveness of the innovative NEW TRIA MINI Set is captivating. It is available in black, white, or brushed aluminium, and in round or square form. Equipped with a powerful, warm white premium LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



## TECHNICAL DATA

|                             |                   |
|-----------------------------|-------------------|
| Item no.                    | 113976            |
| Rotating or tilting         | tiltable          |
| IP Code                     | IP 20 / IP 44     |
| Impact resistance class     | IK 02             |
| Assembly                    | Recessed          |
| Assembly details            | Ceiling           |
| Primary nominal voltage     | 220-240V ~50/60Hz |
| Secondary power / voltage   | 700 mA            |
| Safety class                | II                |
| Wattage                     | 3.4 W             |
| Minimum ambient temperature | -20 °C            |
| Maximum ambient temperature | 30 °C             |
| Level of inrush current     | 15 A              |
| Duration of inrush current  | 150 µs            |
| Stroboscopic effect (SVM)   | 0                 |
| Lumen                       | 190 lm            |
| Colour temperature          | 3000 Kelvin       |
| Beam angle                  | 30 °              |
| Color                       | aluminium         |
| CRI                         | 90                |
| UGR ≤                       | 19                |
| LXXBXX data                 | L70B50            |

## Light Source

|  |  |
|--|--|
|  |  |
|--|--|

|                       |          |
|-----------------------|----------|
| Service life          | 30000 h  |
| Risk Group            | 1        |
| Height                | 3.6 cm   |
| Diameter              | 5.2 cm   |
| Net weight            | 0.111 kg |
| Gross weight          | 0.139 kg |
| Shape of cut-out      | round    |
| Installation depth    | 4 cm     |
| Installation diameter | 4.5 cm   |
| BIG WHITE Page        | 141      |