




NEW TRIA 1 SET

recessed fitting, LED, 2700K, round, black, 38°, 14W, incl. driver, clip springs

The simplicity and effectiveness of the NEW TRIA 1 SET is captivating. It is available in black, white, or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.	114220
Rotating or tilting	cardanic
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	2 A
Duration of inrush current	80 µs
Stroboscopic effect (SVM)	0.01
Lumen	1010 lm
Colour temperature	2700 Kelvin
Beam angle	38 °
Color	black
CRI	80
LXXBXX data	L70B50



Light Source

916415 

Service life	30000 h
Height	5.3 cm
Diameter	13 cm
Net weight	0.439 kg
Gross weight	0.524 kg
Shape of cut-out	round
Installation depth	6 cm
Installation diameter	11 cm

