



PATTALITE-recessed fitting

LED, 3000K, round, matt white, 38°, incl. driver

The innovative PATTALITE I recessed fitting is suitable for ceiling thicknesses of up to 25 mm. Rated IP65 it can be used outdoors or in damp areas. This set is available in matt black, matt white, or brushed aluminium as well as in round or square form. Equipped with a powerful, warm white premium COB LED in a rigid mount, as well as the dimmable LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.

TECHNICAL DATA

| | |
|----------------------------|-----------------------------|
| Item no. | 114421 |
| IP Code | IP 20 / IP 65 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | II |
| Wattage | 11 W |
| Level of inrush current | 2 A |
| Duration of inrush current | 40 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 910 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 38 ° |
| Color | white |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 40000 h |
| Height | 4.5 cm |
| Diameter | 8 cm |



Light Source

| | |
|--------|---|
| 916451 |  |
|--------|---|

| | |
|-----------------------|----------|
| Net weight | 0.251 kg |
| Gross weight | 0.299 kg |
| Shape of cut-out | round |
| Installation depth | 6 cm |
| Installation diameter | 6 cm |
| BIG WHITE Page | 245 |

