




H-LIGHT 2

recessed fitting, LED, 2700K, oval, black, 20°, 11,5W, incl. driver, clip spring

The H-LIGHT 2 recessed fitting series impresses with its simple and elegant design, the integrated warm-white LED module with its narrow 20° beam angle ensures a discreet and ambience-oriented radiance. Thanks to the LED driver included in the set, the luminaire is immediately ready for connection to a 230V power supply.



TECHNICAL DATA

| | |
|----------------------------|-----------------------------|
| Item no. | 114490 |
| Rotating or tilting | tiltable |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | II |
| Wattage | 11 W |
| Level of inrush current | 2 A |
| Duration of inrush current | 40 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 395 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 20 ° |
| Color | black |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 40000 h |
| Height | 8 cm |



Light Source

| | |
|--------|---|
| 916341 |  |
|--------|---|

| | |
|-----------------------|----------|
| Diameter | 9 cm |
| Net weight | 0.333 kg |
| Gross weight | 0.388 kg |
| Shape of cut-out | round |
| Installation depth | 8 cm |
| Installation diameter | 8 cm |

