



## KADUX 3

recessed fitting, triple-headed, QPAR51, rectangular, matt white, max. 150W, incl. clip springs

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. The lamp holders of this GU10 high-voltage version are multi-directional, allowing individual focus of the light beam. The KADUX 3 recessed fitting comes ready for direct connection to 230V mains.

## TECHNICAL DATA

|                         |                         |
|-------------------------|-------------------------|
| Item no.                | 115531                  |
| Socket                  | GU10                    |
| Number of sockets       | 3                       |
| Rotating or tilting     | rotary Bar and tiltable |
| IP Code                 | IP 20                   |
| Assembly                | Recessed                |
| Assembly details        | Ceiling                 |
| Primary nominal voltage | 220-240V ~50/60Hz       |
| Safety class            | I                       |
| Wattage                 | 50 W                    |
| Color                   | white                   |
| Length                  | 21 cm                   |
| Width                   | 9 cm                    |
| Height                  | 13 cm                   |
| Net weight              | 0.746 kg                |
| Gross weight            | 0.824 kg                |
| Shape of cut-out        | square                  |
| Installation length     | 20 cm                   |
| Installation width      | 8 cm                    |
| Installation depth      | 13 cm                   |
| BIG WHITE Page          | 214                     |



## Recommended lamp

|         |   |
|---------|---|
| 1005079 | LED lightbulb QPAR51 ,<br>GU10, 3000K, white  |
| 1005311 | QPAR51 GU10 tunable<br>smart , white / transparent<br>LED light, 5W<br>2700-6500K CRI90 38° |
| 1005076 | LED lightbulb QPAR51 ,<br>GU10, 2700K, white  |
| 1005082 | LED lightbulb QPAR51 ,<br>GU10, 4000K, white  |

