




SUPROS 78

ceiling light, LED, 3000K, round, black, 60° lens

The SUPROS luminaire impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



TECHNICAL DATA

Item no.	116330
Number of different light outlets	1
Rotating or tilting	tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	12 W
Level of inrush current	30 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.09
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	25000 h



Light Source

916364	
--------	---

Light distribution	rotational symmetric
Light outlet	direct
Height	15.8 cm
Diameter	7.8 cm
Net weight	0.605 kg
Gross weight	0.664 kg

