




## HELIA 50

spot for 1-circuit high-voltage track, LED, 3000K, white, 35°, incl. 1-circuit adapter

Adjustable LED spot HELIA 60 with suitable adapter for the 240V 1-circuit track system. The luminaire impresses with its slim design and is therefore ideal for modern lighting concepts. The luminaire is made from aluminium and equipped with a Premium LED module.



## TECHNICAL DATA

Item no.	143581
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Track Ceiling, Track Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	2 A
Duration of inrush current	50 µs
Stroboscopic effect (SVM)	0.03
Lumen	880 lm
Colour temperature	3000 Kelvin
Beam angle	35 °
Color	white
CRI	90
LXXBXX data	L70B50



## Light Source

916387 

Service life	30000 h
Length	14 cm
Height	12 cm
Diameter	5.5 cm
Net weight	0.363 kg
Gross weight	0.479 kg
BIG WHITE Page	507