



HELIA 40

pendant, LED, 3000K, round, black, 9W

With the HELIA 40 you have a pendant with a purist and clear design. This luminaire is available in black, white and brushed copper. A 9 W warm-white premium LED is integrated, this is supplied from the built-in constant current driver. The luminaire is delivered with a 1.5 m connection lead. This means the luminaire is ready for direct connection to the 230V mains supply.

TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 152370 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 10 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Level of inrush current | 10 A |
| Duration of inrush current | 40 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 730 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 30 ° |
| Color | black |
| CRI | 90 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |



Light Source

| | |
|--------|---|
| 916387 |  |
|--------|---|

| | |
|----------------|----------|
| Length | 45 cm |
| Diameter | 4 cm |
| Pendant length | 150 cm |
| Net weight | 0.899 kg |
| Gross weight | 1.099 kg |
| BIG WHITE Page | 303 |

