




## ENOLA\_C

spot for 240V 3-phase track, LED, 3000K, round, white, 55°, 11.2 W, incl. 3-phase adapter

Turnable and tiltable high-voltage LED spot ENOLA\_C with suitable adapter for the 240V 3-phase track system. Outfitted with a powerful, warm white COB LED, the spot is available in a number of colours, as well as various beam angles. As an accessory for the cylindrical spot, we also offer suitable decorative rings with a textured glass diffuser. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

Item no.	152431
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Track Ceiling,Track Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	1040 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Length	10.7 cm
Height	17.3 cm
Diameter	10 cm



## Light Source

916476 

Net weight	0.699 kg
Gross weight	0.933 kg
BIG WHITE Page	543