






KALU TRACK

spot for 240V 3-phase track, LED, 3000K, round, black, incl. 3-phase adapter

Adjustable KALU TRACK spotlight with suitable adapter for the 3-circuit 240V track system. Designed as an extension of the popular KALU series, this new spotlight takes on the shape of the product family. The built-in LED module guarantees high light output with low power consumption. To meet all lighting requirements, versions with G53 and GX53 sockets for the 1- and 3-circuit systems are available. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	152600
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling, Track Ceiling, Track Wall, Wall
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Safety class	II
Wattage	13 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	3 A
Duration of inrush current	10 µs
Lumen	970 lm
Colour temperature	3000 Kelvin
Beam angle	95 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	25000 h







Light Source

703130	F
--------	---

Length	13.5 cm
Height	17 cm
Diameter	10.5 cm
Net weight	0.497 kg
Gross weight	0.607 kg
BIG WHITE Page	540