



PIREQ GU10 ROUND downlight

matt white, max. 50W, incl. clip springs

The round, high-voltage version of our popular PIREQ QPAR51 recessed fitting series is available with a black, white or aluminium housing. The generous rotation and pivoting range of this recessed spot guarantees you the ability to individually focus its light beam, regardless of whether you choose to use halogen or LED retrofit lamps. Installation is carried out using the factory installed spring clips. The PIREQ QPAR51 recessed fitting is supplied ready for direct connection to a 230V alternating current.

TECHNICAL DATA

| | |
|---------------------------|-------------------------|
| Item no. | 199981 |
| Socket | GU10 |
| Number of sockets | 1 |
| Tilt range | 30 ° |
| Horizontal rotation range | 360 ° |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Safety class | II |
| Wattage | 50 W |
| Color | white |
| Light outlet | direct |
| Height | 11 cm |
| Diameter | 9.3 cm |
| Net weight | 0.179 kg |
| Gross weight | 0.219 kg |
| Shape of cut-out | round |
| Installation depth | 11 cm |
| Installation diameter | 7.8 cm |

Recommended lamp

| | |
|---------|--|
| 1005075 | LED lightbulb QPAR51 , GU10, 2700K, grey |
| 1005273 | QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36° |

