




## DASAR 255

outdoor inground fitting, LED, 3000K, IP67, stainless steel 316, asymmetrical, 34W

The accessible high-voltage inground light DASAR 255 LED SQUARE inground light convinces with its stainless steel screen and glass cover in a partial satin finish. Its IP 67 protection class makes it ideal for outdoor use. In this way, the outdoor inground light LED creates an exciting lighting atmosphere that convinces with a long LED life-span of 25,000 hours. Experience light with SLV – your reliable partner for all kinds of outdoor lights for 40 years.



## TECHNICAL DATA

Item no.	229383
IP Code	IP 65 / IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	750 mA
Safety class	I
Wattage	31 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	18.6 A
Duration of inrush current	240 µs
Temperature at glass (light emission)	41 °C
Stroboscopic effect (SVM)	0.01
Lumen	1660 lm
Colour temperature	3000 Kelvin
Color	stainless steel
CRI	90
LXXBXX data	L70B50



## Light Source

791822	
--------	---

Service life	50000 h
Length	25.5 cm
Width	25.5 cm
Depth	14.5 cm
Net weight	5.854 kg
Gross weight	6.516 kg
Shape of cut-out	square
Installation length	24.5 cm
Installation width	24.5 cm
Installation depth	17.5 cm
BIG WHITE Page	839

