




## OUT-BEAM

outdoor wall light, LED, 3000K, beam up/flood down, anthracite

The OUT BEAM series LED wall light, available in single-headed and double-headed versions, was designed especially as an architectural accent illumination. The LED light sources lie opposite each other and are covered by glass, they produce a narrow and a wide beam respectively and thus create the special up/down effect. Thanks to its IP44 protection class, the luminaire is suitable for outdoor use. The electrical connection of the luminaire is made directly to the 230V mains supply thanks to the built-in LED driver. The OUT BEAM series also includes wall lights for halogen lamps.





## TECHNICAL DATA

Item no.	229665
Number of different light outlets	2
IP Code	IP 44
Impact resistance class	IK 03
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Stroboscopic effect (SVM)	0.01
Lumen	740 lm
Colour temperature	3000 Kelvin
Beam angle	80 °
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Width	15 cm
Height	15 cm



## Light Source

916409	
916416	

Depth	15.8 cm
Net weight	1.556 kg
Gross weight	1.779 kg
BIG WHITE Page	775

