




TERANG 2

outdoor wall and ceiling light, LED, 3000K, IP44, oval, white, max. 11W

A new interpretation of the classical construction luminaires for wall and ceiling mounting with a pre-installed powerful LED module. Available with housing colours of white, silver-grey, anthracite and rust, the TERANG 2 XL has frosted round glass, which guarantees homogeneous distribution of its light. With protection class IP44, this luminaire is also designed for use outdoors. Thanks to its pre-installed LED driver, the TERANG 2 is ready for direct connection to a 230V mains supply.




TECHNICAL DATA

Item no.	229931
IP Code	IP 44
Impact resistance class	IK 03
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling, Wall
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Stroboscopic effect (SVM)	3.6
Lumen	830 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	20000 h
Width	19.8 cm
Height	11 cm
Depth	7.5 cm



Light Source

954795	
--------	-----------------------------------------------------------------------------------

Net weight	0.457 kg
Gross weight	0.557 kg
BIG WHITE Page	817

