




LOGS 70

outdoor floor stand, LED, 3000K, IP65, square, anthracite, L/W/H 13/8/69,5 cm, 8W

The indirect LED floor stand LOGS 70 is made from aluminium and equipped with a high-performance planar LED. Depending on the version various housing heights and colours are available. The required driver for direct connection to 230V mains supply is included in each package. For simplified mounting, a suitable earth-spike, screw set and junction box are available on accessory. In addition, the installation can be extended by wall lights of the series.



TECHNICAL DATA

Item no.	232125
IP Code	IP 65
Impact resistance class	IK 04
Assembly	Surface
Assembly details	Ground
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	9.5 W
Maximum ambient temperature	40 °C
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	570 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Width	13 cm
Height	69.5 cm
Depth	8 cm

Light Source

916376	
--------	---

Accessories

231230	EARTH SPIKE , for GRAFIT, RUSTY SLOT, LOGS floor stand, galvanised steel, length 48cm
228730	CONNECTION BOX , 3-pin, IP68
228754	SCREW SET , stainless steel, M5, incl. plugs and washers.
232119	CONCRETE ANCHOR SET , for LOGS floor stands, stainless steel

Net weight	2.993 kg
Gross weight	4.039 kg
BIG WHITE Page	633