


H-POL

pathway and floor stand, single-headed, LED, 3000K, anthracite, L/W/H 16.5/16.5/66 cm

The H-POL SINGEL indirect radiating floor stand is made of aluminium and plastic. With protection class IP55, it is suitable for outdoor use. Thanks to the 8W LED, the luminaire is ideal for use as a pathway light. The product is designed for floor installation and is through-wireable. A large mounting pot is available for optimum mounting in the earth. Thanks to the built-in LED driver, it can be connected directly to the 230V mains supply.



TECHNICAL DATA

Item no.	232165
IP Code	IP 65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Recessed
Assembly details	Ground,Ground with Acc.
Number of through-wires	18
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	17 A
Duration of inrush current	35 µs
Stroboscopic effect (SVM)	0.01
Lumen	700 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	30000 h



Light Source

916393	
--------	---

Accessories

232195	MOUNTING POT , for H-POL pathway and floor stand, anthracite
--------	--

Risk Group	0
Length	16.5 cm
Width	16.5 cm
Height	66 cm
Net weight	2.358 kg
Gross weight	3.154 kg
Shape of cut-out	square
Installation length	11.8 cm
Installation width	11.8 cm
Installation depth	10 cm
BIG WHITE Page	676

