# 7811/W



Flex Lightline, with SMD2216 LEDs, 192LEDs/meter, 10W/meter.Supplied in 5 meters roll .

Can be cut every 3cm.

Avoid direct sunlight.

Requires 24V DC constant voltage LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP67 90 CRI DIMMABLE

## Downloads

IES


## Dimensions





## Gallery




## Accessories



7811E



7811F

## Related items



20030

## Physical Specification

| | |
|---|---|
| Item Group | 07 Strips & Profiles |
| Family | Neon Flex Lightlines |
| Order Code | 7811/W |
| Material | Silicone |
| Shape | Rectangular |
| Length | 5000mm |
| Width | 10mm |
| Surface Ceiling | Yes |
| Surface Wall | Yes |
| Surface Floor/Ground | Yes |
| Indoor | Yes |
| Outdoor | Yes |

## Electrical Characteristics

### Fitting

| | |
|---|---|
| Input Type | Constant Voltage |
| Input Voltage | 24V DC |
| Safety Class | III |
| Power(Watts) | 10W/m |
| IP Rating | IP67 |
| Light Source | LED built in |
| LED Type | SMD 2216 |
| LED Brand | Epistar |

| | |
|---|---|
| LED Number | 192LEDs/m |
| F Mark |  |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K |
| Lumen Output | 550lm/m |
| Light Efficiency | 55lm/W |
| CRI | 90 |
| Illumination Diagram |  |

## Packing Info

| | |
|---|---|
| Box Length | 32cm |
| Box Width | 32cm |
| Box Height | 2,5cm |
| Box Weight | 0.780kg |
| Pcs/Carton | 40 |
| Barcode | 5291889055815 |
| HS Code | 9405423100 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 3 years |