05 Downlights Fixed>UGR19 CCT V Range

10113UV/W/V



13W SMD LED UGR19 downlight with adjustable CCT, IP44.

Complete with 300mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP44 IK04 90 CRI UGR19 CE

Downloads


IES

Dimensions



Gallery





Physical Specification

Item Group	05 Downlights Fixed
Family	UGR19 CCT V Range
Order Code	10113UV/W/V
Colour	White
Material	Die Cast
Shape	Circular
Height	40mm

Diameter	135mm
Cutout Hole Diameter	120mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Adjustable	No
IK Rating	4

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	13W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	300mA
Voltage	38V
Safety Class	III
Power(Watts)	6,84W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 2835

LED Brand	Epistar
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,3-12,6W
Power Factor	0,9
Constant Current	Yes
300mA	25-42V
IP Rating	IP44
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload

Illumination Data

Colour Temperature	3000K-4000K-6000K
Lumen Output	975lm
Light Efficiency	75lm/W
CRI	90
Illumination Diagram	
UGR	19

Packing Info

Box Weight	0.360kg

Pcs/Carton	20
Barcode	5291889065302
HS Code	9405413990

Certification & Warranty

Warranty	3 years