06 Downlights Fixed LED>The Dark Light Dome Reflector Die cast 10116FD/W/BS



16W LED Dark Light Dome Reflector, IP20.

Complete with 300mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 80 CRI DARK LIGHT CE

Downloads

IES

Dimensions



Gallery



Physical Specification

Item Group	06 Downlights Fixed LED
Family	The Dark Light Dome Reflector Die cast
Order Code	10116FD/W/BS
Colour	White-Brass
Material	Die Cast
Shape	Circular
Height	50mm

Diameter	170mm
Cutout Hole Diameter	155mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	300mA
Voltage	50V
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan

F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13,5-18W
Power Factor	0,9
Constant Current	Yes
300mA	45-60V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Kegu
Protection	Short Circuit and Overload

Illumination Data

Colour Temperature	3000K
Lumen Output	800lm
Light Efficiency	50lm/W
CRI	80
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	19,5cm
Box Width	17,5cm

Box Height	5,5cm
Box Weight	0,38Kg
Pcs/Carton	20
Barcode	5291889065593
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Average Lifetime	30000hrs
Weee Directive	Yes