04 Recessed Spots Adjustable LED>The 6,5W COB Recessed Cylinders 11107C/W/W



6,5W COB LED recessed adjustable spot, for general lighting applications.

Requires 700mA constant current LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



89008A



89008AT

Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The 6,5W COB Recessed Cylinders
Order Code	11107C/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	85mm
Diameter	90mm
Cutout Hole Diameter	83mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	9,3V
Safety Class	III
Power(Watts)	6,5W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	F

Illumination Data

Colour Temperature	3000K
Lumen Output	550lm
Light Efficiency	84lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	10cm
Box Width	10cm
Box Height	10cm
Box Weight	0.297kg
Pcs/Carton	36
Barcode	5291889049241
HS Code	9405413990

Certification & Warranty

Warranty	5 years