13 Wall & Ceiling LED>LED Decorative Cylinders

12112T/W/W



12W COB LED adjustable ceiling light.

Complete with black and brass reflectors.

Supplied with 350mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	LED Decorative Cylinders
Order Code	12112T/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	95mm
Diameter	80mm
Recessed Ceiling	Yes
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	350mA
Safety Class	
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6,5-9,5W
Power Factor	0,9

Constant Current	Yes
350mA	27-38V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KEGU
Protection	Short Circuit Protection,Overload Protection,No-load Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1080lm
Light Efficiency	90lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.505kg
Pcs/Carton	20
Barcode	5291889076520
HS Code	9405413990

Certification & Warranty

Warranty	5 years